

Description

Dual center tap Schottky rectifier designed for high frequency Switched Mode Power Supplies.


Features

- High junction temperature capability
- Good trade off between leakage current and forward voltage drop
- Low leakage current


Applications

- Switching Power Supply
- Industrial Application
- Computer and Peripheral
- Home Appliance
- Consumer Product
- Battery Charger/Adapter
- LCD Monitor/TV
- AC-DC Converter
- DC-DC Converter
- Telecommunication
- Free Wheeling Diodes
- Polarity Protection

Marking Information and Pin Configurations (Top View)



TO - 220FPAB & TO - 220AB




TO - 3P

40: Maximum average forward rectified current - 40A
H: Low V_F family
100: Repetitive peak reverse voltage - 100V
C: Dual Cathode Common
A: Assembly Location
Y: Year
WW: Work Week

Ordering Information

ORDERING NUMBER	PACKAGE	SHIPPING
GMR40H100CTB3T	TO220AB	50 Units/ Tube
GMR40H100CTBF3T	TO220FPAB	50 Units/ Tube
GMR40H100CTP3T	TO-3P	30 Units/ Tube

Block Diagram



Absolute Maximum Ratings

PARAMETER	SYMBOL	VALUE	UNITS
Repetitive Peak Reverse Voltage	V_{RPM}	100	V
RMS Forward Current	$I_{F(RMS)}$	40	A
Peak Forward Surge Current 8.3ms single half sine-wave superimposed on rated load (JEDEC METHOD)	I_{FSM}	300	A
Maximum Operating Junction Temperature	T_J	175	°C
Operating storage temperature	T_{STG}	-45 to +150	°C
Voltage Rate of Change	dV/dt	10,000	V/ μ s
Electrostatic Discharge Voltage. JEDEC Method. ESD HBM. Contact	V_{ESD}	± 8	kV



Thermal Characteristics

PARAMETER	SYMBOL	TO220AB	TO220FPAB	TO-3PF	UNITS
Typical thermal resistance	Θ_{JC}	2.4	4.2	1.2	°C/W

Electrical Characteristics (per diode) $T_J = 25^\circ\text{C}$, Unless otherwise noted


PARAMETER	SYMBOL	Test Condition	Min	Typ	Max	Units
DC Forward Voltage	V_F	$I_F = 20\text{A}$		0.78	0.80	V
Average Rectified Forward Current	$I_{F(AV)}$				20.0	A
Maximum Reverse Current	I_R	$V_R = 100\text{V}$	-	-	5	μA
		$V_R = 100\text{V}, T_J = 125^\circ\text{C}$		-	6	mA

Package Outline Dimensions – TO220AB




Unit: mm

Package Outline Dimensions – TO220FPAB



Package Outline Dimensions – TO-3P



Ordering Number

GM **R** **40** **H** **100** **C** **TBF3** **I**

APM
Gamma
Micro

Circuit
Type:
Rectifier

Rated
Current
40A

Low V_F
Family

Rated
Voltage
100V

Dual
Cathode
Common

Package
TB3: TO220AB
TBF3: TO220FPAB
TP3: TO-3P

Shipping
T: Tube
R: Tape & Reel